					DOMESTIC	DOMESTIC				
YMBOL	FIXTURE	TRAP	WASTE	VENT	COLD WATER	HOT WATER		DESCRIPTION	MANUFACTURER	MODEL
WC-A	WATER CLOSET (ACCESSIBLE)	INT.	3"	2"	1/2"		FIXTURE:	FLOOR MOUNTED, FLUSH VALVE, VITREOUS CHINA, ELONGATED 17" HIGH	AMERICAN STANDARD	3043.102
							FLUSH VALVE:	FLUSH VALVE: DIAPHRAGM TYPE, 1.6 GALLONS PER FLUSH POLISHED CHROME PLATED BRASS	SLOAN	111-XL
							SEAT:	SEAT: OPEN FRONT, STAINLESS STEEL HINGE POSTS		
L-A	LAVATORY (ACCESSIBLE)	1-1/4"	2"	2"	1/2"	1/2"	FIXTURE:	WALL MOUNTED, 20" x 18", VITREOUS CHINA, ADA ACCEPTABLE FAUCET LEDGE, 4" CENTER FAUCET HOLES	AMERICAN STANDARD	0355.012
							FAUCET:	SINGLE LEVER, CHROME PLATED BRASS	SYMMONS	S-20-2-LP-FR
							17,0021.	0.5 GPM LAMINAR FLOW RESTRICTOR	OMNI	A-200
							DRAIN:	CHROME PLATED BRASS, POP-UP, CHROME PLATED BRASS OFFSET, CHROME PLATED BRASS TAILPIECE.	Civil Vi	N 200
							TRAP:	TRAP: POLISHED CHROME PLATE 17 GA. BRASS 1/2" CHROME PLATED BRASS TUBE	J.R. SMITH	2698-CP
							SUPPORT:	CONCEALED ARM, FLOOR MOUNTED, FLOOR PLATE		
							SUPPLIES:	POLISHED RIGID CHROME PLATED BRASS TUBING		
							STOPS	POLISHED CHROME PLATED BRASS ANGLE BALL VAVLE		
KS	SINK (BREAK RM/KITCHEN)	1-1/2"	2"	2"	1/2"	1/2"	FIXTURE:	SINGLE COMPARTMENT, 304 STAINLESS STEEL, 16" X 16" BOWL	JUST	SL-2219-A-GR
11.5	SHAK (BREAK KW) KITOHEN)	1 1/2		2	1/2	1/2	I IXTORE.	8" DEEP, 4-1/2" FAUCET LEDGE, SELF RIMMING,	0031	SL ZZIS A ON
							FAUCET:	DECK MOUNTED, MIXING FAUCET, CHROME PLATED BRASS,	JUST	J-1174-KS
							TAGGET.	6-1/2" SWIVEL GOOSENECK SPOUT, 5" WRIST HANDLES	0031	0 1174 113
								2.0 GPM LAMINAR FLOW RESTRICTOR	OMNI	A-200
							TRAP:	POLISHED CHROME PLATE 17 GA. BRASS	OWNT	7. 200
							SUPPLIES:	POLISHED RIGID CHROME PLATED BRASS TUBING		
							STOPS	STOPS: POLISHED CHROME PLATED ANGLE BALL VAVLE		
							ADA:	WHITE PREFORMED INSULATED P-TRAP & VALVE ASSEMBLY	TRUEBRO	103
MS	MOP SINK	3"	3"	2"	1/2"	1/2"	FIXTURE:	FLOOR MOUNTED, ENAMELED CAST IRON, VINYL RIM GUARD	AMERICAN STANDARD	7741.000
							DRAIN:	CHROME PLATED BRASS GRID DRAIN	OUIOAGO FALIOFT	907 OD 00 IVOE
							FAUCET:	WALL MOUNTED, VACUUM BREAKER SPOUT, WALL BRACKET POLISHED CHROME PLATED BRASS, INTEGRAL STOP DEEP SEAL CAST IRON P—TRAP	CHICAGO FAUCET	897-CP-GCJKCF
EWC-2	ELECTRIC WATER COOLER	2"	2"	2"	1/2"	1/2"	FIXTURE:	ELECTRIC, BI-LEVEL, REFRIGERATED, 8.0 GPH AT 80 F., ARI 1010	ACORN	A112108F
		_	_	_	., _	,,-	TRAP:	SCHEDULE 40 PVC		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
							SUPPLIES:	POLISHED RIGID CHROME PLATED BRASS TUBING		
							STOPS:	POLISHED CHROME PLATED ANGLE BALL VAVLE		
								DIELECTRIC COUPLING		
			- 44	- 44			SUPPORT:	SUPPORT: FLOOR MOUNTED, BOTTOM BEARING PLATE		
FD-T	FLOOR DRAIN	2"	2"	2"			FIXTURE	GENERAL DUTY, TRAP PRIMER CONNECTION 5" ROUND NICKEL BRONZE GRATE	J. R. SMITH	2010-A-P
	CLEANOUT		SAME AS PIPE				TRAP:	DEEP SEAL P TRAP	CHARLOTTE PIPE	NH-50
CO FCO	FLOOR CLEANOUT		SAME AS PIPE SAME AS PIPE				EQUIPMENT: EQUIPMENT:	CAST IRON BLIND PLUG HEAVY DUTY NICKEL BRONZE TOP, BRASS PLUG	J. R. SMITH	NH-50 4113S-NB
COTG	CLEANOUT TO GRADE		SAME AS PIPE				EQUIPMENT:	HEAVY DUTY NICKEL BRONZE TOP, BRASS PLUG HEAVY DUTY NICKEL BRONZE TOP, BRASS PLUG	J. R. SMITH	4113S-NB 4113S-NB
1.(1)!!=										

ACCEPTABLE MANUFACTURERS

DRAINAGE (FLOOR DRAINS, ETC): J.R. SMITH, ZURN, MIFAB, WATTS, JOSAM, WADE

ELECTRIC WATER COOLER ACORN, ELKAY, HAWS

FAUCETS: CHICAGO FAUCETS, T & S BRASS, SPEAKMAN

FLUSH VALVES (FLUSHOMETERS): SLOAN, COYNEY-DELANY, ZURN, GERBERIT

FIXTURE SUPPORTS: J.R. SMITH, ZURN, MIFAB, WATTS, JOSAM, WADE

VITREOUS-CHINA FIXTURES: AMERICAN STANDARD; KOHLER, ELJER, CRANE, ZURN


PIF	PE INSULATION	REQUIREMENTS
SERVICE	PIPE SIZE	PIPE INSULATION MATERIAL
DOMESTIC COLD WATER	ALL	1" PREFORMED FIBERGLASS WITH ALL SERVICE JACKET PREFORMED PVC FITTING COVERS
DOMESTIC HOT WATER	ALL	1" PREFORMED FIBERGLASS WITH ALL SERVICE JACKET PREFORMED PVC FITTING COVERS

PIPE MATERIAL SCHEDULE					
SERVICE	PIPE MATERIAL	FITTINGS	JOINTS		
DOMESTIC WATER	ASTM B88	ASME B16.18	ASTEM B32		
DISTRIBUTON	TYPE 'L'	CAST COPPER -ALLOY	LEAD FREE SOLDER		
	COPPER TUBING	SOLDER JOINT			
		OR			
		ASME B16.22			
		WROUGHT COPPER			
		SOLDER JOINT			
DRAIN WASTE	ASTM F891,	ASTM D2665	ASTM D2564		
AND VENT	SCHEDULE 40	DRAINAGE PATTERN	SOLVENT CEMENT		
(BELOW GRADE)	CELULAR CORE PVC				
DRAIN WASTE	ASTM F891,	ASTM D2665	ASTM D2564		
AND VENT	SCHEDULE 40	DRAINAGE PATTERN	SOLVENT CEMENT		
(ABOVE GRADE)	CELULAR CORE PVC				
		DRAINAGE PATTERN	SOLVENT CE		

	VAL	LVE SCHEE	ULE
SERVICE	VALVE TYPE	PIPE SIZE	DESCRIPTION
DOMESTIC WATER	BALL	2" &	COPPER ALLOY, 2-PIECE, STANDARD PORT
SERVICE	VALVE	SMALLER	CHROME PLATED BALL, TFE SEAT,
			LEVER HANDLE
			400 PSIG WOG, MSS SP-110
			SOLDERED OR THREADED END
	CHECK	2" &	BRONZE BODY, SPRING TYPE, TFE SEAT
	VALVE	SMALLER	BRONZE DISC, SOLDERED OR THREADED ENDS
			MSS SP-80
	UNION	2" &	ASTM B16.39, CLASS 150, MALLEABLE IRON,
		SMALLER	HEXANGONAL STOCK BODY,
			BRONZE-TO-BRONZE SEAT

VOLUME FILL MBOL MANUFACTURER MODEL NO. (GALLONS) PRESSURE	
MODEL 1 MARIOTACTORER MODEL NO. (GALLONS) FRESSORE	COMMENTS
T-1 AMTROL ST-5 2 55	(1)

			INPUT		WATER TEMP	
SYMBOL	MANUFACTURER	MODEL NO.	BTU	GPH	RISE (DEG F)	COMMENTS
WH-1	BRADFORD WHITE	M-I-30S6FBN	30,000	31	90	(1)



SYMMETRY FIRST
ARCHITECTS,

8600 Foundry Street
Box 2069
Savage, MD 20763
240-568-0700
240-568-0354 fax
www.symmetryfirst.com

STAMP

PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND.

LICENSE NO. 38508

EXPIRATION DATE: MARCH 03, 2012

NOTE: THESE DRAWINGS ARE THE PROPERTY OF SYMMETRY FIRST ARCHITECTS, LLC AND, AS SUCH, MAY NOT BE REPRODUCED OR RE-USED, EITHER WHOLLY OR IN PART, WITHOUT PRIOR WRITTEN CONSENT OF SYMMETRY FIRST ARCHITECTS, LLC.

PROJECT PHASE

BID

DOCUMENTS

PROJECT TITLE

A.O.C. TENANT BUILD-OUT

2001COMMERCE PARK DR., SUITE 2001-B ANNAPOLIS, MD 21401

REVIS				
REVISIONS				
DATE	ISSUED FOR			
10.21.11	PERMIT REVISION			

PROJECT NUMBER 11-160

DATE 9.1.11

SCALE AS NOTED

DRAWING TITLE

PLUMBING SCHEDULES

SHEET NUMBER

P.601